

RTD CALIBRATOR

CC-02

HTCTM
INSTRUMENTS

Features:

- RTD CALIBRATOR.
- Accuracy $\pm 0.02\%$

OHM measurement :

Output RANGE	INPUT ACCURACY $\pm\Omega$	
	4 WRITE	2 WRITE AND 3 WRITE
0.00 Ω -400.00 Ω	0.1	0.15 Ω
400.0 Ω -1500.0 Ω	0.5	1 Ω
1500.0 Ω -3200.0 Ω	1.0	1.5

OHM Simulate :

RANGE	Output accuracy $\pm\Omega$	Allow excitation(mA)
0.00 Ω -400.00 Ω	0.1	0.1~3.0
400.0 Ω -1500.0 Ω	0.5	0.05~0.8
1500.0 Ω -3200.0 Ω	1.0	0.05~0.4

RTD specification :

RTD TYPE	Range $^{\circ}\text{C}$ ($^{\circ}\text{F}$)	Accuracy($^{\circ}\text{C}$)			Allowable Excitation(mA)
		INPUT		OUTPUT	
		4w	2w/3w		
Pt1093850	-200.0~800.0(-328.0~1472.0)	1.5	1.5	1.5	0.1~3.0
PT50(385)	-200.0~800.0(-328.0~1472.0)	0.3	0.5	0.5	0.1~3.0
PT100(385)	-200.0~800.0(-328.0~1472.0)	0.3	0.4	0.4	0.1~0.3
Pt200(385)	-200.0~630.0(-328.0~1166.0)	0.2	0.4	0.4	0.1~0.3
Pt500(385)	-200.0~630.0(-328.0~1166.0)	0.2	0.4	0.4	0.05~0.8
Pt100(385)	-200.0~630.0(-328.0~1166.0)	0.2	0.4	0.4	0.05~0.4
Pt100(385)JIS	-200.0~800.0(-328.0~1472.0)	0.3	0.4	0.4	0.1~3.0

- **Standard Accessories** : Test Lead, Hostler, Manual
- **Dimension** : 190(H) x 89(W) x 42(D)mm

