

TEMPERATURE MONITORING SYSTEM



Temperature Monitor is an economical Server Room & Data Center Facilities Temperature Monitor which simultaneously measures, displays & alerts user about the critical parameter of Temperature in IT Infrastructure facilities.

The Temperature Monitor has a wall mounting display unit with Single line 4 Digit 7 Segment LED Display displaying the temperature of the server room/data center. The Sensor is a wired sensor with Standard wire length of 3 mtrs, which enables the display monitor to be placed outside the server room / data center room & the sensor can be placed inside the room being monitored.

The Room Temperature Monitor has an Integrated Programmable Buzzer alarm for alerting in case of any deviation from customer specified temperature Low & high limits.

Specifications:

Temperature Measuring Range	: 0.0 ... 60.0 Deg.C
Accuracy	: +/-0.5 Deg.C +/-1 Count
Display Type	: 4 Digits for Temperature , 0.4 " Height , RED LED Display
Alarm Type	: In-Built Buzzer for Low Limit & high Limit Exceed Alarms for Temperature limit violation alert
Acknowledgement Key	: Provided to re-set the alarm, thus avoiding continuous buzzer alarm. However, the alarm LED continues to glow indicating limit violation alert of temperature
Alarm limits	: Freely programmable from front key pad for both low & High
Power Supply	: 24 V.D.C by way of 230 VAC , 50 Hz Adaptor provided alongwith
Cable Length	: Connecting cable, pre-wired 3 mtrs. Extension between display monitor & sensor.
Enclosure Type	: Wall Mounting type ABS Plastic Enclosure with wall Bracket
Enclosure Size	: 80 (W) x 80 (H) x 55 (D) mm.

Instrukart Holdings

India Toll Free: 1800-121-0506 | Ph: +91(40)40262020 | Mob: +91 7331110506

Email : info@instrukart.com | Web: www.instrukart.com

#18, Street 1A, Czech Colony, Sanath Nagar, Hyderabad-500018, INDIA.



INSTRUKART

YOUR WORLDWIDE INSTRUMENT PARTNER