

Anemometer

AVM-06

HTCTM
INSTRUMENTS

Features:

- Used for ambient temperature, humidity, dew point temperature, wet bulb temperature, wind speed, and air volume.
- Large-screen LCD and backlight
- Data Hold
- Auto Power OFF
- USB real time data uploading functions.



Technical Data :

Air Velocity

Basic Functions	Range	Resolution	Basic Accuracy
m/s (meter/Second)	0.80 ~ 30.00 m/s	0.01 m/s	±(2.0% reading + 50 characters)
km/h (kilometers/Hour)	1.40~108.00 km/h	0.01km/hr	
Ft/s (Feet/Second)	1.30 ~ 98.50 ft/s	0.01ft/S	
Knots(Nautical MPH)	0.80 ~ 58.30 knots	0.01 knots	
mil/h (Mil /Hour)	0.90 ~ 67.20 mil/h	0.01mil/h	
ft/m (Feet/Minute)	78 ~ 5900 ft/m	1ft/m	

Air Volume

CFM	0~99990	(Area) 0 - 9.999 ft ²	
CMM	0~99990	(Area) 0 - 9.999 m ²	
CMS	0~99990	(Area) 0 - 9.999 m ²	
Ambient temperature, dew point temperature, wet bulb temperature	-10°C~60°C	0.1°C	±1.5°C
	14°F~+140°F	0.1°F	±2.7°F
Relative humidity	(20~80)%RH	0.1%RH	±3%RH@25°C
	(<20 or >80)%RH	0.1%RH	±5%RH@25°C

- **Standard Accessory** : Battery, Hard Carrying Case, Manual, Software CD, USB Cable
- **Dimension** : 165 (H) * 85 (W) * 38 (D) MM

Buy online @ www.instrukart.com