

# DIGITAL ANEMOMETER

Model : AM-4200

ISO-9001, CE, IEC1010



**Lutron**

**LUTRON ELECTRONIC**

***The Art of Measurement***

# ANEMOMETER

Model : AM-4200

FEATURES	
* High quality with the economical cost.	* Battery power source from 006P DC 9V batteries.
* Pocket & compact housing case.	
* Separate probe, convenient for the remote measurement.	
* Low-friction ball vane wheels is accurate in both high & low velocities.	
* Multi-functions for air flow measurement: m/s, km/h, ft/min, knots. mile/h.	
* Fast and accurate readings with LCD display.	* Used the durable, long-lasting components, including a strong, light weight ABS-plastic housing case.
	* Wide applications: use this anemometer to check air conditioning & heating systems, measure air velocities, wind speeds, temperature...etc.

GENERAL SPECIFICATIONS			
Display	13 mm ( 0.5" ) LCD. 3 1/2 digits	Power Supply	006P DC 9V battery (heavy duty type).
Measurement	m/s (meters per second)	Power Current	Approx. DC 6 mA.
	km/h (kilometers per hour)	Weight	381 g/0.84 LB.
	ft/min (feet/per minute)	Dimension	Main instrument: 180 x 73 x 23 mm (4.3 x 2.9 x 1.4 inch).
knots (nautical miles per hour)	Sensor head : Round, 72 mm Dia.		
Sensor Structure	Conventional twisted van arm and low friction ball bearing design.	Weight	260 g/0.58 LB ( including battery ).
Sampling Time	Approx. 0.4 sec.	Accessories Included	Instruction manual..... 1 PC. Sensor probe..... 1 PC.
Operating Temperature	0 °C to 50 °C (32 °F to 122 °F).		
Operating Humidity	Less than 80% RH.		

ELECTRICAL SPECIFICATIONS (23± 5°C)			
Measurement	Range	Resolution	Accuracy
m/s	0.8 - 30.0 m/s	0.1 m/s	Full scale : ± ( 3 % + 2 d )
km/h	2.8 - 108 km/h	0.1 km/h	
knots	1.6 - 58 knots	0.1 knots	
ft/min	160 - 5900 ft/min	10 ft/min	
Note: <i>m/s - meters per second      km/h - kilometers per hour</i> <i>ft/min - feet/per minute      knots - nautical miles per hour (international knot)</i>			

OPTIONAL ACCESSORIES	
Holster	High quality rubber protective holster. Model : HS-02

\* Appearance and specifications listed in this brochure are subject to change without notice.

'0609-AM4200

Temp | Humidity | Pressure | Differential Pressure | Vacuum | Gases | Particle | Air Flow  
Moisture | Dissolved Oxygen | Radiation | Air Quality | Light / Lux | Distance | Vibration

**Instrukart**

Ph : +91 (40)40262020 | Mob : +91 88865 50506;

Email : info@instrukart.com | www.instrukart.com

Head Office: #18,Street-1A, Czech Colony, Sanath Nagar, Hyderabad -500018, INDIA.

